


Dual NPN+PNP Small Signal Transistor



Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package:** SOT-363S
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102C

■ Maximum Ratings ($T_a=25^\circ\text{C}$ Unless otherwise specified)

TR1 PNP Pin3、4、5

Item	Symbol	Unit	Conditions	Value
Device marking code				K27
Collector-base voltage	V_{CBO}	V	$I_C = -10\mu\text{A}, I_E = 0$	-60
Collector-emitter voltage	V_{CEO}	V	$I_C = -10\text{mA}, I_B = 0$	-60
Emitter-base voltage	V_{EBO}	V	$I_E = -10\mu\text{A}, I_C = 0$	-5
Collector current	I_C	mA		-600
Power dissipation	P_D	mW		200
Operation junction temperature	T_J	$^\circ\text{C}$		-55 to +150
Storage temperature	T_{STG}	$^\circ\text{C}$		-55 to +150



MMDT2227S

RoHS
COMPLIANT

TR2 NPN Pin1、2、6

Item	Symbol	Unit	Conditions	Value
Collector-base voltage	V_{CB0}	V	$I_C = 10\mu A, I_E = 0$	75
Collector-emitter voltage	V_{CE0}	V	$I_C = 10mA, I_B = 0$	40
Emitter-base voltage	V_{EB0}	V	$I_E = 10\mu A, I_C = 0$	6
Collector current	I_C	mA		600
Power dissipation	P_D	mW		200
Operation junction temperature	T_J	°C		-55 to +150
Storage temperature	T_{STG}	°C		-55 to +150

■ Electrical Characteristics ($T_a = 25^\circ C$ Unless otherwise specified)

TR1 PNP Pin3、4、5

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CB0}$	V	$I_C = -10\mu A, I_E = 0$	-60		
Collector-emitter breakdown voltage	$V_{(BR)CE0}$	V	$I_C = -10mA, I_B = 0$	-60		
Emitter-base breakdown voltage	$V_{(BR)EB0}$	V	$I_E = -10\mu A, I_C = 0$	-5		
Collector-base cut-off current	I_{CB0}	nA	$V_{CB} = -50V, I_E = 0$			-10
	I_{CEX}	nA	$V_{CE} = -30V, V_{EB(off)} = -0.5V$			-50
Emitter-base cut-off current	I_{EB0}	nA	$V_{EB} = -5V, I_C = 0$			-10
DC current gain	h_{FE1}		$V_{CE} = -10V, I_C = -0.1mA$	75		
	h_{FE2}		$V_{CE} = -10V, I_C = -1mA$	100		
	h_{FE3}		$V_{CE} = -10V, I_C = -10mA$	100		
	h_{FE4}		$V_{CE} = -10V, I_C = -150mA$	100		300
	h_{FE5}		$V_{CE} = -10V, I_C = -500mA$	50		
Collector-emitter saturation voltage	$V_{CE(sat)1}$	V	$I_C = -150mA, I_B = -15mA$			-0.4
	$V_{CE(sat)2}$	V	$I_C = -500mA, I_B = -50mA$			-1.6
Base-emitter saturation voltage	$V_{BE(sat)1}$	V	$I_C = -150mA, I_B = -15mA$			-1.3
	$V_{BE(sat)2}$	V	$I_C = -500mA, I_B = -50mA$			-2.6
Transition frequency	f_T	MHz	$V_{CE} = -20V, I_C = -50mA, f = 100MHz$	200		
Delay time	t_d	ns	$V_{CC} = 30V, I_C = -150mA, I_{B1} = -15mA$			10
Rise time	t_r	ns				40



MMDT2227S

RoHS
COMPLIANT

Item	Symbol	Unit	Conditions	Min	Typ	Max
Storage time	ts	ns	$V_{CC}=-6V, I_C=-150mA, I_{B1}=-I_{B2}=15mA$			225
Fall time	tf	ns				60

TR2 NPN Pin1、2、6

Item	Symbol	Unit	Conditions	Min	Typ	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=10\mu A, I_E=0$	75		
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=10mA, I_B=0$	40		
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=10\mu A, I_C=0$	6		
Collector cut-off current	I_{CBO}	nA	$V_{CB}=60V, I_E=0$			10
Collector cut-off current	I_{CEX}	nA	$V_{CE}=60V, V_{EB(off)}=3V$			10
Emmitter cut-off current	I_{EBO}	nA	$V_{EB}=3V, I_B=0$			10
Base cut-off current	I_{BL}	nA	$V_{CE}=60V, V_{EB(off)}=3V$			20
DC current gain	h_{FE1}		$V_{CE}=10V, I_C=0.1mA$	35		
	h_{FE2}		$V_{CE}=10V, I_C=1mA$	50		
	h_{FE3}		$V_{CE}=10V, I_C=10mA$	75		
	h_{FE4}		$V_{CE}=10V, I_C=150mA$	100		300
	h_{FE5}		$V_{CE}=1V, I_C=150mA$	35		
	h_{FE6}		$V_{CE}=10V, I_C=500mA$	40		
Collector-emitter saturation voltage	$V_{CE(sat)1}$	V	$I_C=150mA, I_B=15mA$			0.3
	$V_{CE(sat)2}$	V	$I_C=500mA, I_B=50mA$			1
Base-emitter saturation voltage	$V_{BE(sat)1}$	V	$I_C=150mA, I_B=15mA$			1.2
	$V_{BE(sat)2}$	V	$I_C=500mA, I_B=50mA$			2
Transition frequency	f_T	MHz	$V_{CE}=20V, I_C=20mA, f=100MHz$	300		
Delay time	td	ns	$V_{CC}=30V, I_C=150mA, V_{BE}=-0.5V, I_{B1}=15mA$			10
Rise time	tr	ns				25
Storage time	ts	ns	$V_{CC}=30V, I_C=150mA, I_{B1}=-I_{B2}=5mA$			225
Fall time	tf	ns				60



MMDT2227S

RoHS
COMPLIANT

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	R θ J-A ⁽¹⁾	°C/W	625
Thermal resistance, junction-to-case	R θ J-C ⁽¹⁾	°C/W	500

Note:

(1) Device mounted on PCB, single-sided copper, with standard footprint



■ Characteristics

TR1 PNP Pin3、4、5

Fig 1: Static Characteristics




Fig 2: Dc Current Gain




Fig 3: Collector-Emitter Saturation Voltage




Fig 4: Base-Emitter Saturation Voltage




Fig 5: Base-Emitter On Voltage




Fig 6: Cob/Cib- V_{CB}/V_{EB}







Fig 7: P_D - T_a Curve



TR2 NPN Pin1、2、6

Fig 1: Static Characteristics




Fig 2: Dc Current Gain




Fig 3: Collector-Emitter Saturation Voltage




Fig 4: Base-Emitter Saturation Voltage






Fig 5: Base-Emitter Voltage





Fig 6: Cob/Cib- V_{CB}/V_{EB}






MMDT2227S

RoHS
COMPLIANT

Ordering Information


Preferred P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
MMDT2227S	F2	Approximate 0.009	3000	30000	120000	7" reel
MMDT2227S	F3	Approximate 0.009	10000	/	210000	7" reel

Outline Dimensions



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
E	0.15	0.25	0.35
B	1.15	1.25	1.35
C	2.00	2.10	2.20
P	0.650BSC		
A	1.80	2.00	2.20
T	0.00	0.05	0.100
D	0.90	0.95	1.00
L1	0.20	0.30	0.40
a	4°±4°		
M	0.10	0.15	0.25

Suggested Pad Layout





Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function, or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.